

## SENTINEL 30

The Sentinel 30 is easy to use, easy to move – highly efficient self-contained fire fighting system. When used with First Strike – C-Mine Fire Fighting Foam (C-MFFF), the system is one mean coalmine fire-fighting machine.

### SPECIFICATIONS:

- Height: 28” Width: 29” Length: 66”
- Loaded Weight: 951 lbs. Empty Weight: 709 lbs.
- Hellfighter Mixing Chamber Technology
- Premix Tank: 30 gallon capacity
- Finished Foam Capacity: Approximately 600 gallons
- Discharge Nozzle: 1” CAF Foam w/pistol grip style, 3/4” tip
- Discharge Rate (Max.): 300 gal/min. finished foam
- Discharge Time: 2 minutes
- Foam Discharge Distance: up to 75 feet
- Gas Cylinder (Scuba): 2 – 80 CF 3000 psi
- Regulator: 6000 psi reducing; 0-400 psig
- Dispensing Hose: 1” hard rubber MSHA approved hose
- Hose Length: 50 feet
- Pressure Relief Valve: 200 psi
- Gas Hose: 1/4” 9000 psi test
- Ball Valves: 400 psi
- Check Valves: Two (2) one-way
- Recharge Time: 5 minutes
- Skid Mount

