

SENTINEL 60

The Sentinel 60 is easy to use, easy to move – highly efficient self-contained fire fighting system. When used with First Strike – C-Mine Fire Fighting Foam (C-MFFF), the system is one mean coalmine fire-fighting machine.

SPECIFICATIONS:

- Height: 34” Width: 38” Length: 80”
- Loaded Weight: 1628 lbs. Empty Weight: 1128 lbs.
- Hellfighter Mixing Chamber Technology
- Premix Tank: 60 gallon capacity
- Finished Foam Capacity: Approximately 1200 gallons
- Discharge Nozzle: 1” CAF Foam w/pistol grip style, 3/4” tip
- Discharge Rate (Max.): 300 gal/min. finished foam
- Discharge Time: 4 minutes
- Foam Discharge Distance: up to 75 feet
- Gas Cylinder: Two (2) Nitrogen 150 CF
- Regulator: 6000 psi reducing; 0-400
- Dispensing Hose: 1” hard rubber MSHA approved
- Hose Length: 100 feet
- Hose Reel Capacity: 150 feet
- Pressure Relief Valve: 200 psi
- Gas Hose: 1/4” 9000 psi test
- Ball Valves: 400 psi
- Check Valves: Two (2) one-way
- Recharge Time: 8 minutes

